

# Digital pressure gauge

## Model CPG2400

WIKA data sheet CPG2400



### Applications

- Desk top monitoring of barometric pressure changes
- Production and test environments
- Pressure test benches

### Special features

- Ranges to 6015 psi
- 0.03% FS accuracy
- Absolute, gauge, bidirectional or vacuum
- RS-232 or RS-485 communications
- 17 selectable pressure units and 1 user defined unit
- Two year warranty



Digital pressure gauge, model CPG2400

## Description

### General

Mensor's CPG2400 Digital Pressure Gauge is a low cost, single range pressure measuring instrument. With an accuracy of 0.03% FS and a small package design, this unit is perfect as a desktop pressure monitor or a barometer. The unique design of the CPG2400 provides peak and null features, selectable from the main menu screen. Pressure units are selectable from a choice of 17 different units and one user defined unit. The small package, combined with lower uncertainty levels, make this a perfect choice where high levels of uncertainty are not required and cost is a concern.

### Applications

The CPG2400 is ideal for use as a desktop pressure monitor, barometer, or in production and test environments as a replacement for test gauges. The CPG2400 is temperature compensated from 15 to 45 degrees Celsius and can be used in this range without degradation of accuracy. Pressure ranges are available in either absolute, gauge or bidirectional modes from as low as 10 in.H<sub>2</sub>O to as high as 6015 psi. The price and accuracy of the CPG2400 makes it an ideal replacement for

a mercury manometer in environments where mercury may be a hazard. It is used in the health care industry, weather monitoring (as a barometer), and as a process or laboratory pressure indicator.

### Functional Flexibility

The CPG2400 has a clear LCD display with an intuitive menu structure for easy navigation within the setup screens. A membrane key pad provides the user the capability to navigate within these menus to set display features such as peak, null, pressure units. It also allows access to a password protected calibration section for recalibration of the internal sensor. The CPG2400 can be operated from a remote computer via a RS-232 or RS-485 serial port connection. The serial port can be used to configure, read or calibrate the sensor. This is useful when remote indication of the pressure is required. RS-232 is used for communication over short distances and the RS-485 for longer distances and multidrop applications.

## Specifications

### Model CPG2400

Specifications		
Pressure types		Absolute, gauge, bidirectional
Pressure ranges		Gauge: 0.36 to 6000 psig Absolute: 7.5 to 6015 psia Bidirectional: -0.18 ... 0.18 to -15 ... 6000 psi
Accuracy <sup>(1)</sup>		0.03% FS over compensated temperature range for 180 days.
Resolution		5 digits
Compensated temperature	°C	15 to 45
Storage temperature	°C	-20 to 70
Pressure units		psi, inHg @0°C, inHg @60°F, inH <sub>2</sub> O @4°C, inH <sub>2</sub> O @20°C, bar, mbar, mmHg @0°C, cmHg @0°C, Pa, hPa, kPa, MPa, kg/cm <sup>2</sup> , cmH <sub>2</sub> O @4°C, cmH <sub>2</sub> O @20°C, MSW @0°C
Pressure interfaces		7/16 - 20 SAE, 1/8 and 1/4" FNPT adapters included, 1/16 inch hose barb for reference port
Media compatibility		Pressure port: Clean, dry, non-corrosive, non-combustible, non-oxidizing gases for all rated ranges. Ranges ≥ 7.5 psi: All other media compatible with aluminum, 316 stainless steel, brass, Buna N, Viton, sealant, silicone grease and RTV. Not designed for oxygen service. Reference port: Clean, dry, non-corrosive gases.
Warm-up time	min	<1 minute
Communications		RS-232 or RS-485 (100 ft cable length recommended)
Baud rate	baud	9600 baud, N,8,1
Reading rate	sec	~4.6
Response time	mS	<252
Orientation		Negligible >30 psi zero offset resettable w/zero – can be completely removed with re-zeroing
Power input		12 VDC, .125 A
Display		Monochrome 128x64 LCD, with white LED backlight
Weight	lbs.	<1.5
Case size	in	2.5" H x 4.25" W x 5.22" D
Warranty		One year
Options		Relief valves mounted externally (PN 0014379XXX). Rack mount kit.

1) It is defined by the total measurement uncertainty, which is expressed with the coverage factor (k=2) and includes the following factors: the intrinsic performance of the instrument, the measurement uncertainty of the reference instrument, long-term stability, influence of ambient conditions, drift and temperature effects over the compensated range during a periodic zero point adjustment.

Specifications and dimensions given in this leaflet represent the state of engineering at the time of printing. Modifications may take place and materials specified may be replaced by others without prior notice.

All standard Mensor products are provided with a calibration certificate traceable to NIST. The calibration program at Mensor is accredited to both ISO/IEC 17025:2017 and Z540-1-1994 by A2LA. Mensor is certified to ISO9001:2015.



© 2024 WIKA Alexander Wiegand SE & Co. KG, all rights reserved.  
The specifications given in this document represent the state of engineering at the time of publishing.  
We reserve the right to make modifications to the specifications and materials.  
In case of a different interpretation of the translated and the English data sheet, the English wording shall prevail.



**Mensor LP**  
201 Barnes Drive  
San Marcos, TX 78666 • USA  
Tel. (+1) 512 3964200  
Fax (+1) 512 3961820  
E-Mail sales@mensor.com  
www.mensor.com



**Imported to Europe by:**  
**WIKAI Alexander Wiegand SE & Co. KG**  
Alexander-Wiegand-Straße 30  
63911 Klingenberg • Germany  
Tel. +49 9372 132-0  
Fax +49 9372 132-406  
info@wika.de  
www.wika.de

**Imported to UK by:**  
**WIKAI Instruments Ltd,**  
Unit 6 & 7 Goya Business Park,  
The Moor Road, Sevenoaks  
Kent, TN15 5GY